



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE994M Integrated Circuit Voltage Controlled Oscillator

Description:

The NTE994M is a general purpose voltage controlled oscillator in an 8-Lead DIP type package which may be used to generate square and triangular waves, the frequency of which is a very linear function of a control voltage. The frequency is also a function of an external resistor and capacitor. The NTE994M is specified for operation over the 0°C to +70°C temperature range.

Features:

- Wide Supply Voltage Range: 10 to 24Volts
- Very linear modulation characteristics
- High temperature stability
- Excellent supply voltage rejection
- 10 to 1 frequency range with fixed capacitor
- Frequency programmable by means of current, voltage, resistor or capacitor

Applications:

- FM Modulation
- Signal Generation
- Function generation
- Frequency shift keying
- Tone generation

Absolute Maximum Ratings:

Power Supply Voltage	26V
Power Dissipation (Note 1)	300mW
Operating Temperature Range	0°C to +70°C
Lead Temperature Setting (Soldering, 10 sec)	+300°C

Note 1. The maximum junction temperature of the NTE994M is 100°C. For operating at elevated junction temperatures, devices must be derated based on a thermal resistance of 100°C/W.

Electrical Characteristics: ($V_{CC} = 12V$, $T_A = +25^{\circ}C$ unless otherwise specified)

Parameter	Conditions	Min	Typ	Max	Units
Maximum Operating Frequency	$R_O = 2k$, $C_O = 2.7pf$	-	1	-	MHz
Input Voltage Range Pin 5		$\frac{3}{4}V_{CC}$	-	V_{CC}	-
Average Temperature Coefficient of Operating Frequency		-	200	-	ppm/ $^{\circ}C$
Supply Voltage Rejection	10V to 20V	-	0.1	2	%/V
Input Impedance Pin 5		0.5	1	-	$M\Omega$
VCO Sensitivity	For Pin 5, from 8V to 10V, $f_O = 10kHz$	6.0	6.6	7.2	kHz/V
FM Distortion	± 10 Deviation	-	0.2	1.5	%
Maximum Sweep Rate		500	1	-	MHz
Sweep Range		-	10:1	-	-
Output Impedance	Pin 3 Pin 4	- -	50 50	- -	Ω
Square Wave Output Level	$R_{L1} = 10k$	5.0	5.4	-	V_{p-p}
Triangle Wave Output Level	$R_{L2} = 10k$	2.0	2.4	-	V_{p-p}
Square Wave Duty Cycle		40	50	60	%
Square Wave Rise Time		-	20	-	ns
Square Wave Fall Time		-	50	-	ns
Triangle Wave Linearity	+1V Segment @ $\frac{1}{2}V_{CC}$	-	0.5	1	%

Pin Connection Diagram



